



7630 HYDRAULIC SERVICE CRANE

7,500-lb Capacity with 30' of Reach

Part of the redesigned 76 Series, Stellar's 7630 Telescopic Crane helps you handle big jobs where extended reach is required. The unique boom design reduces weight while maintaining strength, the compact boom tip provides easier reach into small spaces, and the [CDTpro™ Control System](#) with [Range Finder™](#) technology delivers superior control and communications.

ADDITIONAL INFORMATION

- **Planetary Winch.** Featuring a hydraulic or mechanical brake system, it lifts the maximum crane load and offers the smoothest and fastest speeds in the market today for maximum productivity.
- **CDTpro Control System.** The most advanced crane remote ever. Save time by knowing your crane can lift the load before you set up. The innovative, industry-only Range Finder™ technology provides real-time max lifting capacity from any point around the crane.
- **Flip Sheave with Bar-Style Anti-Two Block.** Stellar's patented flip sheave allows for a shorter horse head profile, allowing for boom placement in tight quarters, such as an equipment cab.
- **Octagonal Boom.** This next-generation telescopic service crane boom design optimizes all the features of a hexagonal boom while reducing weight.
- **Superior Boom Articulation.** Stellar Hydraulic Cranes make loading easier with industry-leading -10 degrees to +80 degrees articulation.
- **Full Hydraulic Extension.** No manual extension is required. You get full hydraulic reach of 30'.
- **Crane Boost System:** This industry-first, proprietary technology from Stellar allows operators who reach maximum capacity to productively operate through that situation by effectively increasing crane capacity to nearly 118% of its normal operating mode for a short period of time.
- **Quick-Release Snatch Block Stow.** Easily stow your snatch block on the underside of the boom after use. The unique design gently releases the snatch block for use when the boom is raised at close to 60 degrees to ensure a safe and orderly deployment.
- **On-Demand Speed Control.** This Stellar exclusive ramps engine rpm up only when the crane is being used, returning it to idle after five seconds to lower fuel consumption and reduce noise pollution in the work area.
- **400-Degree Rotation System.** The cast iron base and internal mechanical stop provide the most durable rotation system found in the industry.
- **Counterbalance Valves.** Included on each cylinder to prevent unintended cylinder movement should a hose break.
- **Greaseable Pivot Bushings.** Each pivot pin location includes bushings and grease zerks to simplify maintenance and help ensure years of use.
- **Certified.** Meets ANSI B30.5 and OSHA 1910.180 specifications.

SPECIFICATIONS

Crane Rating*:	44,840 ft-lb (6.2 tm)
Boom Length:	13' 4" (4.06 m) from CL of crane
Boom Extension:	
• 1st Stage:	Hydraulic 100" (254 cm)
• 2nd Stage:	Hydraulic 100" (254 cm)
Maximum Horizontal Reach:	29' 8" (9.04 m) from CL of crane
Maximum Vertical Lift:	31' 6" (9.62 m) from crane base
Lifting Capacity**:	7,500 lbs @ 5' 10" (3,400 kg @ 1.78 m)
	1,535 lbs @ 29' 2" (696 kg @ 8.89 m)
Boom Elevation:	-10° to +80°
Stowed Height (crane only):	38.6" (98 cm)
Mounting Space Required:	20" x 21" (50.8 x 53.3 cm)
Approximate Crane Weight:	1,715 lbs (778 kg)
Winch:	
• Rope Diameter:	3/8" (0.95 cm) 6X31 IWRC-DGXIP X 100' (30.48 m)
• Line pull speed:	60 ft/min (18.29 m/min)
• Max. single part line:	3,750 lbs (1,700 kg)
• Max. double part line:	7,500 lbs (3,400 kg)
Rotation:	400° power (worm gear)
Power Supply Required:	PTO & Pump

8 gpm @ 3,000 psi (30.3 lpm @ 207 bar)

Min. Rec. Chassis (GVRW) 19,000

*Crane rating in Boost Mode. Normal crane rating is 38,000 ft-lbs (5.25 TM).

**Maximum capacities in Boost Mode.

Capacity Chart

Dimensions

Geometric Dimensions



190 State Street | Garner, Iowa 50438 | | 800.321.3741

© Stellar. All rights reserved.

[Manage consent](#)